

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) Found original corner post firmly set and marked (Record - set a post 4 inches square, 4 ft. long, 2 ft. deep, scribed 3-7684.) from which:

A larch 14 in. diam. bears N320W-14.5 ft., snag with all scribing visible. (Record - A blazed tamarack tree, 12 inches in diameter, scribed 3-7684 BT, bears  $N32^{OW} - 14.5 \text{ ft.}$ 

A pine 12 in. diam. bears S4<sup>O</sup>E- 10.0 ft., down and decayed. (Record - A blazed pine tree, 12 inches in diameter, scribed 3-7684 BT, bears S4OE, 10 Ft.,)

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/4/70

For cor. no. 3 "Survey No. 7684"

I set a 2 in. galvanized iron pipe 24 inches in the ground, with

brass cap marked.

I set corner in exact center point of original wooden post from which: A larch 5 in. diam. bears \$100 E - 13.10 Ft., marked RM A larch 6 in. diam. bears \$110 W - 5.6 Ft., marked RM

I placed signs and paint on BT's and at corner

7684

SJS 2532 S 1970

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from Original Field Notes)

		DIAGRAM OF CORNER:
Surveyor's Seal	I,	N. T27N R31W 3 MS 7684
	I, Stanley J. Skousen certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.  Signature of Surveyor	Corner recorded on the she

Registration Number

Lincoln Office of Clerk and Recorder, County of .... This "corner record" was filed for record on the 20. 19....., was noted on the cross-index plat and is assigned page No. 229 in book No... Cross Index No. G - H - 20-2/ T - 27 R. 3/ Mer.