DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found rotted remains of original corner post. (Record-set a fir post 4 ins. square, 4 ft. long,  $1\frac{1}{2}$  ft. deep, square 8-8797.) from which:

A fir 20 In. diam. bears S43<sup>o</sup>30'W - 58.6 ft., snag with all scribing visible. (Record-A blazed fir tree 18 ins. Dia., scribed B.T. 8-8797, bears S42<sup>o</sup>30'W, 58.6 Ft.)

A fir 16 in. diam. bears S34°15'E - 63.3 ft. down and rotted (Record - A blazed fir tree 16 ins. dia., scribed BT. 8-8797, bears S34° 15'E, 63.3 ft.)

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/3/70

For cor. No. 8 "Johnstone Placer" MS 8797

I set a 2 in. galvanized iron pipe 24 inches in the ground at the exact center point of the original wooden post, with brass cap marked from which:

8797

8 JP

A spruce 6 in. diam. bears S68½°W - 13.10 ft., marked RM A Douglas fir 8 in. diam. bears N 64½°W - 15.8 Ft., marked RM

SJS 2532 S 1970

I placed signs and paint on BT's and at corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes)

Surveyor's	Seal	•	
Surveyor's	Seal	•	

I, ....A...R...Trenkle..and.Harold..Etienne......certify that the information shown herein is true and correct.

10

N. T 27N R31W

DIAGRAM OF CORNER:

↑ | 8 JP MS 8797

Signature of Ground Party Chief

a.R. Trenklo

Stanley J. Skousen

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Janely J. Skouses

(Signature of Surveyor

2532 - S Registration Number = Corner recorded on the sheet