

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 12 and 13, T28N R27½W, MPM.
Found original stone firmly set and plainly marked (Record - set a granite stone, 15 X 10 X 8 ins., 10 ins. in the ground, for closing cor. of secs. 12 and 13, marked cc on W, with 4 grooves on S. and 2 grooves on N. faces.) from which:

A pine, 5 ins. diam. bears S40° 30'W, 8 lks. dist., down and decayed
(Record - a pine, 4 ins. diam. bears S40° 30'W, 8 lks. dist., marked T28N R27½W S 13 BT.)

A larch, 8 ins. diam. bears N 74°30'W, 40 lks. dist., alive with all scri bing visible.
(Record - A tamarack, 6 ins. diam., bears N 74° 30'W, 40 lks. dist., marked T.28N R27½W S 12 BT.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 8/10/70

New BT

A larch, 9 ins. diam. bears S 82½°W - 29 lks., marked RM

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes.)

Surveyor's Seal

A. R. Trenkle and Joe French

I,
certify that the information shown herein is true and correct.


A. R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen
Signature of Surveyor

DIAGRAM OF CORNER:



= Corner recorded on the sheet

2532 -S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 30th day of April 1971, was noted on the cross-index plat and is assigned page No. 226, in book No. 1

Eleanor L. Vaughn By: *Mac Watson*, Deputy
County Official

Cross Index No. J25 T. 28 R. 27½ Mer.