

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 24 and 25, T28N R27½W, MPM
Found original stone firmly set and plainly marked (Record - set a limestone,
15 X 12 X 10 ins., 10 ins. in the ground, for closing corner of secs. 24 and 25,
marked cc on W. with 2 grooves on S. and 4 grooves on N. faces, from which:

A larch 53 ins. diam. bears S 24° 30'W, 60 lks. Dist., stump with scribing visible.
(Record - A tamarack, 48 ins. diam., bears S 24°30'W, 60 lks. dist., marked
T28N R27½W S 25 BT.)

A larch 14 ins. diam. bears N 8° 15'W, 88 lks. dist., stump with scribing visible.
(Record - A tamarack, 12 ins. diam. bears N 8°15'W, 88 lks. dist., marked
T28N R27½W S24BT.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 6/29/70.....

New BT.

A lodgepole pine 10 ins. diam. bears S11°W - 153 lks., marked T28N R27½W S 25 BT

None other available

I placed signs and paint on BT and at corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)


(Record from original G.L.O. field notes.)

Surveyor's Seal

A. R. Trenkle and Joe French

DIAGRAM OF CORNER:

I,
certify that the information shown herein is true and
correct.



A.R. Trenkle
Signature of Ground Party Chief
Stanley J. Skousen

= Corner recorded on the sheet

I,
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

Stanley J. Skousen
Signature of Surveyor

2532 - S
Registration Number

Office of Clerk and Recorder, County of Lincola

This "corner record" was filed for record on the 20th day of April 1971, was noted on the cross-index plat and is
assigned page No. 227, in book No. 1

Eleanor L. Vaughn By: *Max Watson*
County Official Deputy

Cross Index No. 885 T. 28 R. 27½ Mer.