CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 13 and 24, T28N R27½W, MPM

Found original stone shattered and loosely set (Record - set a limestone, 20 X 12 X 10 ins. 15 ins. in the ground, for closing cor. of secs. 13 and 24, marked cc on W, with 3 grooves on S and 3 grooves on N. faces.) from which:

A pine, 10 in. diam. bears S17°30'W - 33 lks., alive with scribing visible. (Record - a pine, 8 ins. diam. bears S17° 30'W, 33 lks. dist., marked T28N r27½W S 24BT.)

A larch, 13 in. diam. bears N68⁰45'W -62 lks., alive with scribing visible. (Record - A tamarack, 8 ins. diam. bears N 68⁰45'W, 62 lks. Dist., marked T28N R27½W S 13 B.T.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

I set corner from record bearing and distance from two BT's, and buried the shattered remains of the original corner stone alongside the iron pipe.

I placed signs and paint on BT's and at corner.

S 13 T 28N CC R 27W S 24 S 18 R27½W SJS 2532 S 1970

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal	
-----------------	--

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same,

Signature of Surveyor

DIAGRAM OF CORNER:

N. T28N

S 13
cc
S 24

\$27½W

\$27½W

= Corner recorded on the sheet

2532 -S Registration Number

Office of Clerk and Recorder, County of Lincoln	
~! (1971, was noted on the cross-index plat and is
assigned page No. 228 in book No.	Edeanow L. Vaughn, By: Mae Winter !
i sook 210mm	County Official Deput
	Cross Index No. N. 25 T. 2 R. 2 2 Mer.