CERTIFIED CORNER RECORDATION


Corner 1/4 Secs. 7&18 T. 28N R. 27W P.M., MT Lincoln County

I. <u>1891 G.L.O. Record by Newton Orr:</u> Set a limestone, 18x8x6 ins., 12 ins. in the ground for the 1/4 sec. cor. of secs. 7 and 18, mkd. "1/4" on S. face.

Established two bearing trees:

A tamarack, 18 ins. diam., bears N85°E, 35 lks. dist., mkd "1/4 S BT". A tamarack, 18 ins. diam., bears S57°W, 83 lks. dist., mkd "1/4 S BT".

1978 B.L.M. Record by Larry A. Christiansen: The 1/4 sec. cor. of secs. 7 and 18, monumented with a limestone, 18x8x6 ins., firmly set, 12 ins. in the ground, mkd. "1/4" on the N. face, and witnessed by the original bearing trees. At the corner point, set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a supporting mound of stone, 4.0 ft. base, to top, with brass cap mkd. as shown.



Bury the original stone alongside the iron post.

II. Found a 2 1/2 in. diam. iron pipe, firmly set, in a mound of stone, protruding 2 ins. above the ground, with a 3 1/4 in. diam. brass cap, mkd. as shown, and witnessed by the remains of the original bearing trees.

from which:

A fallen larch, 28 ins. diam., bears N85°E, 23.1 ft. dist., with a healed face. A larch snag, 28 ins. diam., bears S57°W, 54.8 ft. dist., with a healed face.

III. Established two new bearing trees:

A larch, 15 ins. diam., bears S77°W, 90.15 ft. dist., mkd. "1/4 S18 BT". A pine, 8 ins. diam., bears N44°W, 13.2 ft. dist., mkd. "1/4 S7 BT".

Painted bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East

