

CERTIFIED CORNER RECORDATION

Corner W1/4 CORNER SEC.28 T. 28N R. 27W P.M.M. County LINCOLN


RECORD : NONE

FOUND : 5/8" REBAR WITH 3 1/4" ALUM CAP STAMPED AS SHOWN.

MAINTENANCE: SET 5 FOOT STEEL POSTS 2 FEET NORTH AND 2 FEET EAST OF CORNER.

STEEL POST

STEEL POST



SKETCH OF CORNER

CERTIFICATION

DAN CROFT
certify the information shown herein is true and correct.

Signature Ground Party Chief

MARC J. CARSTENS
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

[Signature]
Signature of Surveyor & Seal



Date: 12-2010 Reg. No. 5940 LS

Employer: CARSTENS LAND SURVEYING

Office of Clerk and Recorder, County of LINCOLN, This "corner

record" was filed for record on 230616 BOOK: CCR CC&R'S PAGE: 11742 Pages: 1

STATE OF MONTANA LINCOLN COUNTY
RECORDED: 01/05/2011 3:30 KOI: CC&R'S

TAMMY D. LAUER CLERK AND RECORDER

book No. FEE: \$0.00


BY: [Signature] Deputy

TO: CARSTENS LAND SURVEYING P.O. BOX 1374, POLSON, MONTANA

Cross Index No. U-09 T. 28N R. 27W PMM

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

Sec. 28



• corner this sheet