DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 3 and 4, T.28N R.27W, MPM
Found original stone firmly set and plainly marked (Record - Set a limestone
15 X 12 X 8 ins. 10 ins. in the ground, for closing cor. to Secs. 3 and 4,
marked C.C. with 3 notches on E and W faces,) from which:

A pine 16 ins. diam. bears S20°W - 17 lks. dist., snag with all scribing visible. (Record - A pine 14 ins. diam. bears S20°W - 17 lks. dist. marked T28N R27W. cc S4 BT.)

A larch 21 ins. diam. bears N29°E - 10 lks. dist., stump with BT. visible. (Record - A tamarack 20 ins. diam. bears N29°E - 10 lks. dist. marked T28N R27W cc S 3 & 4 BT.)

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 6/26/70.....

New BT'S

A Douglas fir 8 ins. diam. bears S55°E - 18 lks., Marked RM

A lodgepole pine 9 ins. diam. bears S140W - 5 lks., marked RM

I placed signs and paint on BT'S and at corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

I, A. R. Trenkle and Joe French...
certify that the information shown herein is true and correct.

A.R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same.

of Surveyor

.....2532 -S..... Registration Number DIAGRAM OF CORNER:

N. T29N R27W

S 35 50 60

S 4 S 3

CC
T 28N

= Corner recorded on the sheet

Office of Clerk and Recorder, County of Linco n

This "corner record" was filed for record on the 20th day of Clark 1971, was noted on the cross-index plat and is assigned page No. 225, in book No.

Elianary Linguis By Mar Water of Cross Index No.

Cross Index No.

T. 29 R. 27 Mer.