

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found stone set firmly in place as described.

24" Pine, S84W 26.0' lying face down with visible scribing
26" Fir Stump N 61E, 35.9'


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: June 1980

Set a 2 1/2" X 30" Aluminum pipe with cap marked:
Raised a mound of stone around cap.
Buried original stone alongside cap.
From which:

11" Pine bears N 72 W, 43.4'
marked 1/4 S3 BT
8" Fir bears N 11 E, 33.5'
marked 1/4 S2 BT

Attached signs and painted a 6" red band around trees.



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal




I, Gary Crismon
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, Stephen D. Staab
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:



◆ = Corner recorded on the sheet

5619-S
Registration Number

Office of Clerk and Recorder, County of Lincoln
This "corner record" was filed for record on the 4th day of February 1981, was noted on the cross-index plat and is assigned page No. 999, in book No. 1
Eleanor L. Vaughn, by Michel Groom
County Official Deputy
Cross Index No. C-17 T. 28N R. 27W Mer.