ED CORNER RECORDAT

Corner 1/4 Cor. S 4|3 T. 28 N., R. 28 W., P.M.M. Lincoln

Record:

1902 GLO Township Subdivision by B. Adams

40.00 chs. "Set a Limestone, 18x10x6 ins. 12 ins. in the ground, for 1/4 Sec. Cor. marked 1/4 on W. face, from which:

A fir 8 ins. diam. bears N 45°15' E, 55 lks. dist. marked 1/4 S3 BT. A fir 14 ins. diam. bears N 66°30' W, 23 lks. dist. marked 1/4 S4 BT.

Found Evidence:

The corner for Sec. 3 and 4 monumented with a limestone 17x9x5 ins., firmly set 10 ins. in the ground, marked 1/4 on the W. face, from which:

A Douglas Fir 20 ins. diam. bears N 46° E, 40.80 ft. dist. (record N 45°15' E, 36.30 ft.), with visible scribing.

A Douglas Fir snag with visible root crown bears N 60° W, 16.50 ft. dist. with visible scribing.

Perpetuation:

At the found stone monument position, we replaced it with a 2 ½ inch diam. alum. pipe, 30 ins. long, 20 ins. in the ground, with a 3 1/4 inch dia. alum. cap marked as shown below, from which:

A Douglas Fir 6 1/4 in. diam. bears N 80° W, 7.10 ft. dist., scribed (1/4 S4 BT).

Paint scribed faces red with 6 inch wide bands around both Bearing Trees.

Attached Bearing Tree and Attention Land Survey Monument signs to both trees.

Set a steel post 6 ft. long, 2 ft. in the ground, which bears N 3.00 ft. dist., with attached Property and Land Survey Monument decals.

Raise a collar of stone 2 ft. diam., 1 ft. high, around set monument.

Bury the original stone alongside the set alum. monument.

Cross Index No. 1/4 Cor. S 4|3 T. 28 N., R. 28 W., PMM

| Declination: 18° East | | |
|---|---|--|
| Sketch of Corner | NAD DouglAs FIR Signat I, K certify me or 170422 USA I, JC certify Signat I, K certify me or 170422 Signat Date: | RTIFICATION ohn Damon y the information shown herein is true and correct ALL ALLOY atture of Ground Party Chief Kenneth E. Davis y that this Corner Record correctly at bress his work performed by r under my direction in compliance with the "Corner Recordation Act" 2-101, et-seq., M.C.A.) KENNETH E. DAVIS A 1975 S Reg. No. 4975 S Reg. No. 4975 S Over: Davis Surveying, Inc. |
| Office of Clerk and Recorder, County of This "corner record" was filed for recowas noted on the cross-index planand in book No. | old on <u>8-3-98</u> | Section SEC4 |

• THIS COR