								<u></u>	
		CERTIFIED	COF	RNER	REC(ORD			
Corner	W1/4 SEC. 9	T. 28N	R	29W	P.M.	М.	County LINCO	<u>)LN</u>	
ECORD:	24" TAMARACK BE	6X12X4 ABOVE GROUND WIT ARS N59°E 28.08' SCRIBED 1. ARS N48 1/2°W 112.20' SCRIB	4 S9 BT.		OM WHICH:				
OUND: (X6 ABOVE GROUND WITH 1/4 ARS N60°E 28.0' SCRIBED 1/4		Γ, FROM WI	НІСН:				
NTENAN		H FROM CORNER AREA. SET	5 FOOT S	TEEL POST	T ALONGSID	E OF C	ORNER		
		I°W 11.30' SCRIBED 1/4 RM. S AND PAINTED A RED 6" BA	ND AND S	CRIBE RED)				
							,		
							A 32* 7	TAMARACK	
						۰۰۰	·E		
						1/8	Q		
	12" FIR	S84°W 11.30			_				
	1								
		•							
					T	 -	CE	ERTIFICATION	
						l,	DAN CROFT	true and correct.	
							Clanation	e Ground Party Chief	<u> </u>
	_ /						IARC J. CAR.	STENS	
	\sim	\ \frac{1}{2}				perform	that this Corner Record corrections of the correction of the cord	r in compliance with	WARC I
		4				8	h/t	\Rightarrow	59401.5
							40.0044	re of Surveyor & Seal	SUR
		SKETCH OF CORNEI	ь			Date: Employ	CARSTENS	•	
	· ·			TL!- P-					
	Clerk and Recorder, C	County of LINCOLN 235736 BOOK: C	CR CC	This "c ar's		1920	Pages: 1	Sec. 9	
record" v	was filed for record or	STATE OF MONTANA L	INCOLN	COUNTY					
was note	ed on the cross-index	TRECORDED: 11/02/20 TAMMY D. LAUER CL				.).	9_ A		
book No)	FEE: \$0.00	BY	Ean	rie de	Eun	w deputy		
		TO: CARSTENS LAND SUF		P.O. BOX	1374, POL	•	CHTANA		
		Cross Index No_	G-9	T26	8N R.	29W	PMM		

• comer this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors