INSTRUCTIONS

1. Original and/or s quent record used to evaluate the corner position 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- Description of monument and accessories set to perpetuate the corner position.
 Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

P.M.M. Lincoln Corner <u>1/4 of Secs 15 & 16</u> T 28N R. 29W _County

(Record) nSet a quartz stone 14x22x5, 9 ins in ground marked $\frac{1}{4}$ on N. face.

Stone marked nated and lying loose on the ground. (Found)

(Record) Pine 9" diam. bears S15°W 60 lks. (Found) Pine 14" diam. with scrib partly overgrown bears S15°W, 39.6'

(Record) Pine 36" diam bears N7110E 43 lks. (Found) Pine 36" diam bears N780E 46.1" with scrib grown over.

(Note) As both bearing trees could not fit the G.L.O. notes I set the corner from the south B.T. As there were vary old line tree blazes that best fit this position.

 $30"x2\frac{1}{2}"$ post with $3\frac{1}{2}"$ diam alum. cap in the ground and (Set) and buried the stone alongside.



