1. Original and/or s uent record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of es

Description of monument and accessories set to perpetuate the corner position.
Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

Certification must be signed and scaled by Registered Land Surveyor in State of Montana
Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner E 1/4 Sec. 15 T. 28N R 29W Lincoln \_\_\_ P.M.M. \_\_ \_\_ County (Record)G.L.O. Set a shale stone 14x10x6 9" in ground with 1/4 on W. Face. From which Fir 16" diam. bears  $N24^{\circ}W$  22 lks 1/4 S15 BT Hemlock 6" diam. bears S74°E 51 lks. 1/4 S14BT set an iron post 30"x2½" with brass cap marked Sec. 14 & 15 1964 from which: (Record)B.1.m. both orig. BTs with record dist. and bearings Fir 7" diam. bears S89°E 30 lks. 1/4 S14BT (new) Bim Monomer AS NOTED Orig @.L.O. B.T. for Sec. 15 on ground Stump of B.L.M. Bt bears S89°E 19.8' (Found) (Set)

Set a 6' steel post app. 3.0' North of monument and marked new B.T.s as follows: Fir 4" diam. bears S75°W 8.0' scribed 1/4 S15 BT White Fir 8" diam. bears N36°E 17.7' scribed 1/4S14BT



