

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original stone set firmly in place as described.
From which: Stump bears S 85½ W, 23.8 feet
partial scribing visible

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a 2½" X 30" Aluminum pipe with cap marked:
Raised a mound of stone around corner.


Date of work: June 1980

From which a 6" Fir bears S. 78 W, 14.9 feet
marked S18 BT

6" Pine bears N 40 W, 13.0 feet
marked S7 BT

8" Pine bears N 63 E, 13.3 feet
marked S8 BT

7" Fir bears S 48 E, 22.8 feet
marked S 17 BT



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Attached signs and painted a 6" red band around trees.

Surveyor's Seal



I, Stephen D Staab
certify that the information shown herein is true and
correct.

Signature of Ground Party Chief


I, Stephen D Staab
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

Signature of Surveyor

5619-S
Registration Number

DIAGRAM OF CORNER:

N. T 28N R29W



◆ = Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1981, was noted on the cross-index plat and is
assigned page No. 998, in book No. 1

Eleanor L. Vaughn by Michele Groom,
County Official Deputy

Cross Index No. J-5 T. 28N R. 29W Mer.