## -CERTIFIED CORNER RECORDATION


30W P.M., MT Lincoln **County** Corner 1/4 35&36 T. 28N R. Secs.

1900 G.L.O. Record by Burton S. Adams: Set a pine post, 3 ft. long, 5 ins. square, 24 ins. in the I. ground, for 1/4 sec. cor. mkd. "1/4 S35" on W. and "36" on the E. Face.

Established two bearing trees:

A tamarack, 16 ins. diam., bears S85°70'E, 83 lks. dist., mkd. "1/4 S36 BT". A pine, 22 ins. diam., bears N54°45'W, 44 lks. dist., mkd. "1/4 S35 BT".

1964 B.L.M. Remonumentation Record by Richard L. Larimer: The 1/4 sec. cor. of secs. 35 and 36, monumented with a disintegrated wooden post, firmly set in the ground, and witnessed by one of the original bearing trees. At the corner point, set an iron post, 30 ins. long 2 1/2 ins. diam., 27 ins. in the ground with brass cap mkd. as shown.



Established one new bearing tree and bury the remains of the original wooden post alongside the iron post.

Found a 2 1/2 in. diam. iron post, firmly set, protruding 5 ins. above the ground, with a 3 1/4 in. diam. II. B.L.M. brass cap, mkd. as shown.

from which:

A 6 ft. larch stump, 26 ins. diam., bears S85°E, 54.8 ft. dist., with visible scribe. (GLO-record) A down larch snag, 8 ins. diam., bears S72°W, 9.2 ft. dist., with visible scribe. (BLM-record)

III. Established one new bearing tree and set one post:

> A larch, 8 ins. diam., bears N24°E, 10.8 ft. dist., mkd. "1/4 S36 BT". A galvanized steel guard post, South, 3.0 ft. dist of the corner with a Land Survey Monument decal attached.

No other trees available.

Painted bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East

