

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION


Corner NW Sec. Cor S10 T. 28 N. R. 30 W. P.M.M. Lincoln County

- I. 1900 G.L.O. record by Burton S. Adams: Set a sandstone, 16x12x8, 11 ins. in the ground, and four bearing trees.

1964 BLM Remonumentation by R. L. Larimer & H. W. Grusing: The cor. of secs. 3, 4, 9 & 10, monumented with a sandstone, 16x12x8 ins., firmly set and mkd. with 3 grooves on the E., and 5 grooves on the S faces, and witnessed by the remains of the original bearing trees.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.



From which

The remains of the original bearing trees:

- A stump, 15 ins. diam., bears N 67 1/4° E, 17 lks. dist.
 A stump, 18 ins. diam., bears S 51 1/4° E, 17 lks. dist., mkd. T28N R30W S10 BT.
 A stump, 18 ins. diam., bears S 60° W, 52 lks. dist., mkd. T28N R30W S9 BT.
 A fir, 19 ins. diam., bears N 33 1/2° W, 5 lks. dist., visible marks S4 BT.

The new bearing trees:

- A hemlock, 10 ins. diam., bears N 8° E, 19 lks. dist., mkd. T28N R30W S3 BT.
 A hemlock, 9 ins. diam., bears S 58 1/2° E, 33 lks. dist., mkd. T28N R30W S10 BT.
 A fir, 8 ins. diam., bears S 53° W, 19 lks. dist., mkd. T28N R30W S9 BT.


Bury the original stone alongside the iron post.

- II. Found a 2 1/2 in. diam. iron pipe, 8 ins. above ground, firmly set, with a 3 1/4 in diam. BLM brass cap mkd. as shown above, from which:

- A burnt and down fir, 18 ins. diam., bears N 33° W, 3.3 ft. dist. (5 lks.), no visible marks. (GLO)
 A hemlock snag, 9 ins. diam., bears S 53° W, 12.5 ft. dist. (19 lks.), mkd. T28N R30W S9 BT. (BLM)

The corner falls in a clearcut that has been burned and therefore no trees within reasonable distances are available for new bearing trees.

- III. Set a 6 ft. steel post with Land Survey Marker and Property Boundary decals, West, 3 ft.
 Magnetic Declination: 20° East



SKETCH OF CORNER

CERTIFICATION

Thomas M. Hommel

- I. Thomas M. Hommel
 certify the information shown herein is true and correct.

Signature Ground Party Chief


Alvah F. Hughes

- I. Alvah F. Hughes
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal


Date: 11/18/92 Reg. No. 7322

Employer: U.S. FOREST SERVICE



Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Jan 11, 1993 was noted on the cross-index plat and is assigned page No. 5271, in book No. Coral M. Cummings By JB County Official

Sec. 10



• - corner this sheet

Cross Index No. E-13 T. 28 N. R. 30 W. P.M.M.