

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, not discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner W1/16 S3/S10 T. 28N R. 30W P.M.M. Lincoln County

RECORD:

NONE

FOUND:

A 3/4" iron rod, from which an 8" douglas fir bears N31°E, 11.9 dist., scribed W1/16 S3 BT and a 17" douglas fir bears S28°E, 19.4 dist., scribed W1/16 S10 BT

PERPETUATION:

The corner did not meet positional tolerance specifications. A retracement of the Section Subdivision by Ninneman in 1971, notes a large discrepancy in the location of the East 1/4 corner and conflicting distances between the West 1/4 corner and Northwest Section Corner. The corner was not accepted and a new monument was set this survey.

The new corner position was established as a result of a subdivisional survey of Section 10. Said subdivisional survey was made in accordance with methods and procedures contained in the Manual of Surveying Instructions; U.S. Bureau of Land Management.

Set a standard Forest Service 3 1/4" aluminum cap stamped as shown below, on a 30" x 3/4" aluminum shaft 28" in the ground, from which,

An 8" douglas fir bears N13°W, 5.3 dist., scribed W1/16 S3 BT and a 17" douglas fir bears S4°, 22.2 dist., scribed W1/16 S10 BT

A 6' steel post with Land Survey Monuments decal was placed 2.9 feet south of monument.

Trees were signed and blazes and scribing were painted red.

T28N R30W
S3
W1/16-----
S10
PLS 9958
1993

S 3
PVT
8" D. FIR
BT

17" rod
found

PVT

17" D. FIR
BT FS

S 10
SKETCH OF CORNER

CERTIFICATION

I, John Marquette
certify the information shown herein is true and correct.


John Marquette
Signature Ground Party Chief

I, JAMES R. STAPLES
certify that this corner Record correctly represents work performed
by me or under my direction in compliance with the "Montana
Recordation Act" (70-22-101, et seq., M.C.A.)

James R. Staples
Signature of Surveyor & Seal

Date: 12-20-93 Reg. No. 998LS

Employer: J.R.S. SURVEYING, Inc.



Sec. 10

Office of Clerk and Recorder, County of LINCOLN. This "corner
record" was filed for record on 12-23-93

was noted on the cross-index plat and is assigned page No. 6059 in
book No. _____

Coral M Cummings, by BB
County Official

Cross Index No. AA-9 T. 28N R. 30W PMM