- subsequent record used to evaluate the corner position.
- Description of evidence found, not discrepancies in the record, state method of establishing lost or obliterated or Description of monument and accessories set to perpetuate the corner position.

- Sketch of comer, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 Fill in Cruss Index & Section Diagram at bottom of sheet.

Corner_	E1/16	S10/S15	T. 28N	R	30W	P.M.M	Lincoln	County
RECORD:								
NO	ONE							•
FOUND:								
NO	ONE							

PERPETUATION:

The new corner position was established as a result of a subdivisional survey of Section 10. Said subdivisional survey was made in accordance with methods and procedures contained in the <u>Manual of Surveying Instructions</u>; U.S. Bureau of Land Management.

Set a standard Forest Service $3\frac{1}{3}$ " aluminum cap, stamped as shown below, on a 30" x 3/4" aluminum shaft 27" in the ground, from which:

A 6" douglas fir bears N10°E, 29.6 feet dist., scribed E1/16 S10 BT and A 7" douglas fir bears S22°E, 17.0 feet dist., scribed E1/16 S15 BT

A 6' steel post with Land Survey monument decal attached was placed 6 feet north of monument.

Trees were signed with blazes and scribing painted red.

T28N R30W **S10** E1/16 S15 PLS 9958 1993

