

CERTIFIED LAND CORNER RECORDATION

SECTION 17 Twp. 28 N., R. 33 W., M.P.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original northeast corner of Section 28 in pile of stones with seven B.T.'s

Found original east 1/4 Corner stone for Section 28 with 2 B.T.'s

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Sept. 1973

Set steel rods for 1/16 and 1/64 Corners as shown on diagram ON OTHER SIDE

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE OTHER SIDE

Surveyor's Seal

I, Jack H. Ninneman, certify that the information shown herein is true and correct.

Signature of Jack H. Ninneman, Signature of Ground Party Chief

DIAGRAM OF CORNER:

N. See other Side

I, Jack W. Ninneman, certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Jack W. Ninneman, Signature of Surveyor

= Corner recorded on the sheet

Montana License No. 534 E.S. Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 21st day of November 1973, was noted on the cross-index plat and is assigned page No. 298, in book No. 1

Signature of Eleanor L. Taylor, Deputy County Official

WEST
2645.26'

PILE OF STONES
WITH SEVEN
BEARING TREES.



17

660.05'
500°04'E

S 89°40'31"W

333.80'

500°04'E
661.95'

660.05'
500°04'E

#2

333.81'

333.80'

663.92'

500°17'39"W

667.61'
589°21'02"W

660.05'
500°04'E

671.41'

671.41'

S 89°01'33"W

S 89°01'33"W

#1

663.91'

500°17'39"W

675.21'

660.05'
500°04'E

S 88°42'03"W



ORIGINAL
STONE AND
TWO B.T.

STEEL PINS •

SECTION 17 TWP. 28 N.,
R. 33 W., M.P.M.

No. 1 Found a staub, replaced with a steel pin for C 1/16 E with a 12" larch bearing S 71° W 18.20 feet and a 16" hemlock bearing N 45° E 6.50 feet - both trees are scribed (C 1/16 E B.T.) and posted.

No. 2 Set a steel pin for N 1/16 from which an 18" fir bears N 78° E 64 feet and a 12" fir bears N 37° W 45.70 feet - both trees are scribed (N 1/16 S 16) and posted.