## INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
- Description of evidence found, note the discrepancies in the record, state method of establishing lost or obliterated corners

Corner East 1/16 Corner, Sections 11 & 14 T. 29 N R. 28 W P. M. M. Lincoln

- Description of monument and accessories set to perpetuate the corner position.

  Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories etc.

  Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

  Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

SECTION 14 BREAKDOWN: See corner recordation forms filed concurrently for Section 14 controlling corners. N 89"59"52" E N 89"52"50" E 1318.07 1320.13 1318.07 1320.13 NW 1/4 NE 1/4 1316.28 1316.28 1321.28 1321.28 SEC. 14 1322.43 S 89'48'22" E S 89'48'22" E 00'47'38" 2649.22' DATE OF FIELD WORK: JUNE, 2008 
 • ¼6 CORNERS SET THIS SURVEY
 GROUS SET: A  $\frac{1}{2}$  in. rebar with 2 in. aluminum cap stamped: E 1/16 Geodetic Coordinates: **S**11 NAD83(CORS): LAT. 48°16'59.927"N **S14** LONG. 115°08'02.692"W (for corner reconnaissance) 2008 16734 from which: A 10 inch Fir, bears S 9° W, 27.7 feet, blazed and scribed: BT, tag affixed Joshua Phillips inch Aluminum Adkins WGM Group, SKETCH OF CORNER . This "corner Office of Clerk and Recorder, County of 212981 BOOK: CCR CCER'S PAGE: 11230 STATE OF MONTANA LINCOLN COUNTY was noted RECORDED: 07/22/2008 10:10 KOI: CCER'S \_ , in TAMMY D. LAUER CLERK AND RECORDER book No. . SEC. 14 FEE: \$0.00 TO: FILED , J-20 T. 29 N R. Cross Index No. . Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors corner this sheet