## CERTIFIED LAND CORNER RECORDATION

DESCRIPT	TION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECO	RD (IF KNOWN)
ORIGINAL G.L.O. NOTES:  FOUND:	"Set a trachite stone, 18x14x4 ins., 12 ins. in the ground, for cor. of secs. 14,15,22 and 23, marked with 3 notches on S. and 2 notches on E edges; from which A tamarack, 9 ins. diam., bears N. 73° E., 86 lks. dist., marked T 29 N R 27 W S 14 B T. A tamarack, 12 ins. diam., bears S. 24° 30° E. 61 lks. dist., marked T 29 N R 27 W S 23 B T. A tamarack, 22 ins. diam., bears S. 12° W., 23 lks. dist., marked T 29 N R 27 W S 22 B T. A fir, 4 ins. diam., bears N. 50° W., 22 lks. dist., marked T 29 N R 27 W S 15 B T." FOUND BRASS CAP MONUMENT SET BY THE B.L.M.	•
Ι	DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLE TO PERPETUATE THE ORIGINAL LOCATION OF THIS COR	
	12" Larch overgrown wan blaze blaze Snag  URSE AND DISTANCE TO ADJACENT CORNERS IF DETERM (MAY SKETCH OR PASTE REPRODUCTION ON REVER	T29N R27W e  S15 S14 S22 S23  C401965 OF LAND  MINED IN THIS SURVEY.
SEE (	CERTIFICATE OF SURVEY. NOS. 956 & 957, RECORDS C	OF LINCOLN COUNTY
Surveyor's Seal	certify that the information shown herein is true and correct.  Signature of Ground Party Chief  I. JAMES BURTON certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.  Signature of Surveyor  Signature of Surveyor  5428S  Registration Number	DIAGRAM OF CORNER:  T29N R27W N.  15 14 22 23  = Corner recorded on the sheet
Office of Clerk and Recorder, C This "corner record" was filed assigned page No. 1339	for record on the 14th day of October 1981, was re in book No Cleanor L. Vaug	noted on the cross-index plat and is  My Sherry X. Hawk  inty Official