

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 5 and 6, T29N, R27W, MPM. Found original stone firmly set and marked (Record - set a trachite stone, 20 x 10 x 8 ins., 15 ins. in the ground, for closing cor. of Secs. 5 and 6, marked CC on S., with 5 grooves on E. and 1 groove on W. faces; from which:

A fir, 12 in. diam., bears S 39½°E - 70 Lks. Dist. stump with blaze (Record - a fir, 8 in. diam., bears S 39°15'E - 70 Lks. Dist., marked T29N, R27W, S 5 BT.)

A fir, 8 in. diam., bears S 76¼°W - 26 Lks. Dist., stump with scribing visible, (Record - a fir 7 in. diam., bears S 76°15'W., 26 Lks. Dist. marked T29N, R27W S 6 BT).

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

For the closing cor. common to Sec. 5 and 6, T29N, R27W, MPM,
I set a 2 in. galvanized iron pipe 24 ins. in the ground, with
brass cap marked. I set corner in exact center point of original
stone. From which:

Date of work: Sept. 27, 1971

A 6 in. ponderosa pine bears S 72½°W - 40 Lks. Dist. marked RM.
A 9 in. ponderosa pine bears N 68¼°W - 112 Lks. Dist. marked RM.
I placed signs and paint on RM's and at corner.

S32
T30N R27W
S 6 S 5
T29N R27W
CC
SJS 2532 S
1971

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal

I, A. R. Trenkle and Joe French
certify that the information shown herein is true and
correct.


A. R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

Stanley J. Skousen
Signature of Surveyor

DIAGRAM OF CORNER:



• = Corner recorded on the sheet

2532 - S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 16th day of December 1971, was noted on the cross-index plat and is

assigned page No. 237, in book No. 1

Edmund L. Vaughn, By: Max Watson
County Official

Cross Index No. 45 T. 29 N. R. 27 W. Mer.