

CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found stone in place marked as described (Record - Trachite Stone 20" x 8" x 5", 15" in ground marked $\frac{1}{4}$ on W. face). Sec. 18 BT no evidence found (Record - BT 6" pine marked $\frac{1}{4}$ S 18 BT, bears S 61° 15' W, 20 links). Sec. 17 BT found tipped over - rotted stump as marked (Record - 10" pine marked $\frac{1}{4}$ S 17 BT bears N 51° 30' E, 21 links).


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set GI pipe, 1½" diam., 28" long with brass cap
marked as shown and established new BTs.

Date of work: 7/19/63

New BT 14" fir marked FSRM, bears N 70° 30' E, 36 links.

New BT 10" larch marked FSRM, bears S 50° 00' W, 29 links.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

None

Surveyor's Seal

I, _____
certify that the information shown herein is true and
correct.

Signature of Ground Party Chief

I, _____
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same.

Norman Berg
Signature of Surveyor

1963 S
Registration Number

DIAGRAM OF CORNER:

N. T29N, R27W

18 ♦ 17 $\frac{1}{4}$

= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 8th day of October, 1965, was noted on the cross-index plat and is

assigned page No. 39, in book No. 1

M. M. MANSFIELD, By: *Kerda Hayden*
County Official Deputy

Cross Index No. L-5 T. 29 R. 27 Mer.