

CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 24 and 25, T.29N, R.28W, MPM
 Found original stone shattered and loosely set (Record - set a slate stone,
 24 X 6 X 4 ins., 18 ins. in the ground, for closing corner of Sec. 24 and 25,
 Marked cc on W., with 2 grooves on S. and 4 grooves on N. face.) from which:

A larch 10 ins. diam. bears S 13°W - 78 lks, down and decayed (Record - A tamarack,
 10 ins. diam., bears S 13°W., 78 lks. Dist.; marked T.29N R.28W. S 25 BT.)

A larch 40 ins. diam. bears N 53°45'W - 252 lks, snag with scribing visible.
 (Record - A tamarack, 38 ins. diam., bears N. 53° 45'W., 252 lks. Dist.,
 marked T.29N, R.28W. S 24 BT.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/9/70

I set a 2 in. galvanized iron pipe 24 inches in the ground, with brass cap marked.
 I set corner at the exact center point of the original
 corner stone and buried the shattered remains of the
 original corner stone alongside the Iron pipe. from which:
 A lodgepole pine 6 in. diam. bears S 28°W, 29 lks., marked
 T.29N, R.28W. S 25 CC BT.

T29N
 S 24 | T 29N
 CC | R 27W
 S 25 | S 30
 R 28W
 SJS 2532 S
 1970

A lodgepole pine 6 in. diam. bears N 49½°W, 15 lks., marked
 T.29N, R.28W. S 24 CC BT.

I placed signs and paint on BT's and at corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal

I, A. R. Trenkle and Foe French
 certify that the information shown herein is true and
 correct.

A. R. Trenkle

Signature of Ground Party Chief

Stanley J. Skousen
 I, _____
 certify that I have carefully performed or reviewed the
 work done on the diagrammed corner as reported on this
 recordation form and approve the same.

Stanley J. Skousen

Signature of Surveyor

DIAGRAM OF CORNER:

N. T 29N
 ↑
 S 24 |
 CC | S 30
 S 25 |
 R 28W

= Corner recorded on the sheet

2532 -S
 Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 20th. day of April 1971, was noted on the cross-index plat and is
 assigned page No. 221, in book No. 1

ELEANOR L. VAUGHN, By: *Mac Watson*
 County Official Deputy

Cross Index No. R-25 T. 29 R. 28 Mer.
R-1 29 27