

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)


Found sandstone in place and marked as described (Record-sandstone 14" x 8" x 6", set 9" in ground, marked $\frac{1}{4}$ on W. face) Sec. 22 BT stump found and marked (Record 24" Tamarack marked $\frac{1}{4}$ S 22 BT bears N57°30'W, 28 links) Sec. 23 BT stump found and marked (Record; 30" Tamarack marked $\frac{1}{4}$ S23 BT bears N13°30'E, 15 links

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7-19-63

Set GI Pipe, 1 $\frac{1}{2}$ " diam, 28" long with brass cap marked as shown and established new BT'S. Placed stone at base of GI pipe

New BT-8' Fir, marked FSRM, bears N42°E, 20.71 feet
New BT-30" Tamarack, marked FSRM, bears N48°W, 32.7 feet



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original GLO notes)

Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, Norman Berg
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Norman Berg
Signature of Surveyor

1963-5
Registration Number

DIAGRAM OF CORNER:



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 12th day of April 1968, was noted on the cross-index plat and is assigned page No. 98, in book No. 1

Eleanor L. Vaughan
County Official W. L. Wagon, Dep.

Cross Index No. P-17 T. 29 R. 28 Mer.