

INSTRUCTIONS

VIAN


1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found; note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner CN 1/16 S32 T. 29N R. 29W P.M.M. Lincoln County

1. No Original Record.
2. N/A
3. I set a 28" long 2-1/2 diam. aluminum pipe with a 3-1/4" cap marked as shown below, from which: A 13 ins. diam. Doug Fir bears N17°E 7.60 feet dist. marked CN 1/16 S32 BT and a 10 ins. diam. Doug Fir bears N66°W, 8.90 feet dist. marked CN 1/16 S32 BT.


BTs tagged, corner posted, rock mound and BTs painted red per contract requirements.



SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the 10th day of Nov. 19 81, was noted on the cross-index plat and is assigned page No. 1359, in book No. 1 Eleanor L. Vaughn by Betty L. County Official Concess.

Cross Index No. _____ T. 29N R. 29W P.M.M.



* - corner this sheet

CERTIFICATION

L. A. Dolezal

certify the information shown herein is true and correct.

L.A. Dolezal

MELVIN J. Lauteren
certify that this Corner Record is my original work performed by me or under my direction in accordance with the "Corner Recordation Act" (70-22-101).

Melvin J. Lauteren
Signature of Surveyor or Seal
Date: Nov. 19 81 REGISTERED NO. 4232-S
Employer: Kootenai County Engineering, Inc.