

INSTRUCTIONS

UJAN


1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner SE 1/16 S32 T. 29N R. 29W P.M.M. Lincoln County

1. No Original Record
2. N/A
3. I set a 28" long, 2-1/2" diam. aluminum pipe with 3-1/4" cap marked as shown below from which a 20 ins. diam. Doug Fir bears S13°W, 10.60 feet dist. marked SE1/16 S32 BT and an 11 ins. diam. Doug Fir bears N73°W 32.10 feet dist., marked SE1/16 S32 BT.

BTs tagged, corner posted, rock mound and BTs painted red per contract requirements.



SKETCH OF CORNER

CERTIFICATION

I, L. A. Dolezal

certify the information shown herein is true and correct.

I, Melvin D. Lauterbach
MELVIN D. LAUTERBACH

certify that this Corner Record was performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101) M.C.A. 4-23-25

Date: Sept 2, 1981 4232-S


Employer: Kootenai Engineering, Inc.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the 16th day of Nov. 19 81, was noted on the cross-index plat and is assigned page No. 1362, in book No. 1 Eleanor J. Vaughn by Betty L. Conner

County Official

Cross Index No. 29N R. 29W P.M.M.

Sec. 32



• - corner this sheet