

INSTRUCTIONS


1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner S1/16, S32, S33 T. 29N R. 29W P.M.M. Lincoln County

1. No Original Record.
2. N/A
3. I set a 28" long 2-1/2" diam. aluminum pipe with 3-1/4" cap marked as shown below from which a 9 ins. diam. Grand Fir bears N40°W 48.60 feet dist., marked S1/16 S32 BT and a 7 ins. diam. Doug Fir bears S10°E 15.40 feet dist. marked S1/16 S33 BT.

BTs tagged, corner posted, rock mound and BTs painted red per contract requirements.



SKETCH OF CORNER

CERTIFICATION

I, L. A. Dolezal

certify the information shown herein is true and correct.

I, Melvin P. Lauterbach

certify that the Corner Record shown herein represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101).

Signature of Surveyor Melvin P. Lauterbach

Date: Sept 27 1981


Employer: Kootenai Engineering, Inc.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the 16th day of Nov 19 81, was noted on the cross-index plat and is assigned page No. 136A, in book No. 1

Eleanor L. Vaughn by Betty
County Official L. Conner

Cross Index No. _____ T. 29N R. 29W P.M.M.

Sec. 32



• - corner this sheet