

INSTRUCTIONS

11/11/81


1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

**CERTIFIED CORNER RECORDATION**

Corner SC, E 1/16 S32 T. 29N R. 29W P.M.M. Lincoln County

1. No original record.
2. N/A
3. I set a 28" long 2-1/2" diam. aluminum pipe with 3-1/4" cap marked as shown below, from which a 7 ins. diam., Larch bears N50°E, 17.20 feet dist., marked SC E1/16, S32 BT and a 7 ins diam., Lodgepole Pine bears N65°W, 30.30 feet dist., marked SC E1/16 S32 BT.

BTs tagged, corner posted, rock mound and BTs painted red per contract requirements.




SKETCH OF CORNER

CERTIFICATION

I, L. A. Dolezal  
 certify the information shown herein is true and correct.  
 L. A. Dolezal  
 Registered Land Surveyor  
 I, Melvin D. Lauteren  
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101)  
 MELVIN D. LAUTEREN  
 Registered Land Surveyor  
 Date: Sept. 1981  
 Employer: Keptner Engineering, Inc.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the 11th day of Nov. 1981, was noted on the cross-index plat and is assigned page No. 1365, in book No. 1 Esmeralda Vaughan by Betty  
 County Official L. Cordes



Cross Index No. \_\_\_\_\_ T. 29N R. 29W P.M.M.

- corner this sheet