

CERTIFIED LAND CORNER RECORDATION

1/4 Corner between Secs. 34 and 35 Twp. 29 N., R. 29 W., M. P. M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

N 0° 02' W between Sections 34 and 35

40.0 Ch. Set a granite stone 16X8X6 ins. 11 ins. in ground for 1/4 corner, marked 1/4 on W. face from which

A tamarack 24 ins. in dia. bears N 33° 40' W 39 lks. dist. marked 1/4 S 34 BT

A fir 10 ins. in dia. bears S 68° E 35 lks dist. marked 1/4 S 35 BT.

ALL EVIDENCE DESTROYED

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


Date of work: 5/23/'72

Set a standard brass cap monument in a mound of stone  
from which a tagged post 7 feet high bears east 8.0 feet

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE SIDE

Surveyor's Seal



I, Jack H. Ninneman  
certify that the information shown herein is true and correct.

*Jack H. Ninneman*  
Signature of Ground Party Chief

I, Jack W. Ninneman  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*Jack W. Ninneman*  
Signature of Surveyor

DIAGRAM OF CORNER:

N.  
See reverse  
Side

= Corner recorded on the sheet

Mont. 534  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 25th day of July, 1972, was noted on the cross-index plat and is

assigned page No. 1, in book No. 277

*Eleanor L. Vaughn*  
County Official