CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

This corner was established by survey of Libby Airport

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a 2 inch galvanized iron pipe 24 inches in ground, at exact corner point indicated on plat of this designated corner, with brass cap marked, from which: Date of work: 3/26/70

Libby
Airport
COR 9
1970

A 11 in. Ponderosa Pine bears N. 19° E. - 66 1ks - mkd rm

SJS 2532 S

A 9 in. Ponderosa Pine bears S. 87° W. - 60 1ks - mkd rm

Location, attention and bearing tree signs were posted at the corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Plat attached to reverse side of recordation form for corner no. 9 of survey of Libby Airport.

I,
certify that the information shown herein is true and correct. a. R. Tuenble
Signature of Ground Party Chief
I, STANLEY J. SKOUSEN

N. T 29 N R 30 W

DIAGRAM OF CORNER:

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation, form and approve the same.

Signature of Surveyor

t = Corner recorded on the sheet

2532 S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 6th. day of May 19 70, was noted on the cross-index plat and is assigned page No. 191, in book No. 1

ELEANOR L. VAUGHN, By: Max Wattern County Official Deputy

Cross Index No. 6-/ T. 29 R. 30 Mer.