CERTIFIED CORNER RECORDATION
CORNER E-E-W 1/256 Cor. T. 29 N., R. 31 W., P.M.M. LINCOLN COUNTY
Sec. 1
RECORD: NONE
NOINE
FOUND EVIDENCE:
NONE
•
PERPETUATION:
SET A 3 1/4 INCH ALUMINUM CAP STAMPED (SEE DIAGRAM BELOW) ON A 5/8 INCH DIA.
REBAR 20 INCHES LONG. FROM WHICH
A 7 INCH DBH DOUGLAS FIR SCRIBED X BT. BEARS N 25° W 2.2 FEET.
A 14.5 INCH DBH DOUGLAS FIR SCRIBED E-E-W 1/256 S 1 BT. BEARS S 13° E 6.3
FEET.
PAINTED 6 INCH WIDE BANDS AND ATTACHED BEARING TREE SIGNS TO TREES.
MAGNETIC DECLINATION: 18° E
7" Douglas Fir
CERTIFICATION L. GEORGE CLARK
Cartify the information shown herein is true and correct
T 29 N R 31 W Signature of Ground Party Chief
certify that this Corner Resord correctly represents work
E-E-W 1/256 performed by the of ander my direction in compliance with the
2004 5 13. E 0-12-101, et seq., (M.C.A.)
gnature of surveyor & Sel
14.5" Douglas Fir
SKETCH OF CORNER
$\mathcal{A} \circ \mathcal{A}$ SECTION
180464 BOOK: CCR CCER'S PAGE: 10688 Pages: 1 STATE OF MONTANA LINCOLN COUNTY
CORAL M. CUMMINGS CLERK AND RECORDER
TO: FILED, Separate dennes THE CORNER
Cross Index No. <u>E-E-W 1/256 Cor. Sec. 1</u> T. 29 N., R. 31 W., P.M.M.