CERTIFIED CORNER RECORDATION
CORNER C-E-E-N-W 1/256 T. 29 N., R. 31 W., P.M.M. LINCOLN COUNTY
Cor. Sec. 1
DECORD.
RECORD:
NONE
FOUND EVIDENCE:
NONE
NONE
PERPETUATION:
SET A 3 1/4 INCH ALUMINUM CAP STAMPED (SEE DIAGRAM BELOW) ON A 5/8 INCH DIA. REBAR 20 INCHES LONG.FROM WHICH
REBAR 20 INCHES LONG.F ROM WHICH
A 13 INCH DBH DOUGLAS FIR SCRIBED C-E-E-NW 1/256 S 1 BT. BEARS N 51° W 9.5
FEET.
A 6.5 INCH DBH DOUGLAS FIR SCRIBED X BT. BEARS S 64° E 1 1.4 FEET.
PAINTED 6 INCH WIDE BANDS AND ATTACHED BEARING TREE SIGNS TO TREES.
MAGNETIC DECLINATION: 18° E
13" Douglas Fir
Wa arrange and a second arrange arrang
CERTIFICATION 1. GEORGE CLARK
Certify the information shown herein is true and correct
T 29 N R 31 W
Signature of Ground Party Chief
I, KENNETH E. DAVIS
certify that this Colour Record correctly represents work
C-E-E-NW 1/256 perocent by mer hander my direction in compliance with the
2004 To Confer Recordation acts
To Vis
and up of Surveyor & Stal
6.5" Douglas Fir
Employee Lewis Juny my Tac
CVETCLI OF CODYED
SKETCH OF CORNER
Office of Clerk and Recorder, County of Sencola
180468 BOOK: CCR CCER'S PAGE: 10691 Pages: 1
STATE OF MONTANA LINCOLN COUNTY
RECORDED: 11/08/2004 10:25 KOI: CC&R'S
CORAL M. CUMMINGS CLERK AND REPORDER FEE: \$0.00 BY: Spanned Chapes T
TO: DAVIS SURVEYING, INC. F. 9 BOX 896, TROY, MONTANA 59935
THIS CORNER
Cross Index No. <u>C-E-E-N-W 1/256 Cor. Sec. 1</u> <u>T. 29 N., R. 31 W., P.M.M.</u>