

# CERTIFIED CORNER RECORDATION

CORNER C1/4 T. 29 N., R. 31 W., P.M.M. LINCOLN COUNTY

## RECORD:

NONE

## FOUND EVIDENCE:

NONE

## PERPETUATION:

Set a 5/8 inch dia. rebar 24 inches long with a 3/4 inch Aluminum cap stamped (see diagram below)  
From which:

A 17 inch DBH Douglas Fir scribed C1/4 S10 BT bears N56°W 84.3 ft dist.


A 12.5 inch DBH Lodge Pole Pine scribed C1/4 S10 BT bears S56°E 30.6 ft dist.

Painted 6 inch wide bands and attached bearing tree tags to both trees.

## MAGNETIC DECLINATION: 18° E

17" DOUGLAS  
FIR

N 56° W  
84.3'



DIAGRAM

12.5" LODGE  
POLE PINE

I, George Clark CERTIFICATION

Certify the information shown herein is true and correct  
Signature of Ground Party Chief

I, George Clark

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 6/18/09 Reg. No: 4975-S

Employer: DAVIS SURVEYING INC

## SKETCH OF CORNER

Office of Clerk and Recorder, County of \_\_\_\_\_

This "corner" 219610 BOOK: CCR CC&R'S PAGE: 11296 Pages: 1

was noted c STATE OF MONTANA LINCOLN COUNTY

No. \_\_\_\_\_ RECORDED: 06/18/2009 11:50 KOI: CC&R'S


In book No TAMMY D. LAUER CLERK AND RECORDER

FEE: \$0.00

BY: Tammy D. Lauer

TO: DAVIS SURVEYING, INC P.O. BOX 896, TROY, MONTANA 59935

## SECTION



Cross Index No. C1/4 T. 29 N., R. 31 W., P.M.M.

THIS CORNER