CERTIFIED CORNER RECORDATION CORNER C-W1/16 T. 29 N., R. 31 W., P.M.M. LINCOLN **RECORD: NONE** FOUND EVIDENCE: Found original stone scribed PC 1/16 which bears S12W 31.95 ft. dist. from set monument PERPETUATION: Set a 5/8 inch dia. rebar 24 inches long with a 31/4 inch Aluminum cap stamped (see diagram below) From which: A 9.5 inch DBH Cedar scribed CW1/16 S10 BT bears N10°W 2.7 ft dist. A 10 inch DBH Douglas Fir scribed CW1/16 S10 BT bears S3°E 15.5 ft Painted 6 inch wide bands and attached bearing tree tags to both trees. MAGNETIC DECLINATION: 18° E 9.5" CEDAR Certify the information shown herein is true and correct T29N R31W Signature of Ground Party Chief rendra C-W 1/16 certify that this Corner Record correctly represents work **S10** performed by me or under my direction in compliance with the 2009 10" DOUGLAS DIAGRAM SKETCH OF CORNER **SECTION** Office of Clerk and Recorder, County of This "corner reconst the second control of t PAGE: 11297 was noted on th STATE OF MONTANA LINCOLN COUNTY No. - RECORDED: 06/18/2009 11:51 KOI: CC&R'S In book No. TAMMY D. LAUER CLERK AND RECORDER FEE: \$0.00 TO: DAVIS SURVEYING, INC. P.O. THIS CORNER C-W1/16 Cross Index No. T. 29 N., R. 31 W., P.M.M.