## INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

C	FRTI	FI	FD	CORN	FR	<b>RECO</b>	RD.	ATIO	٨
•			LU	OUILI				$\Delta$ I I $\Delta$	

Corner	S1/4 Sec. 16	T	29 N.	_R	. W.	P.M.M	Lincoln	County		
	G.L.O. Original record by D. P. ing trees.	Mumbrue:	Set a 3 i	t. wood	post	as monumen	t and scribed two	-		
	1963 B.L.M. Remonumentation record by G. F. Pittman et al: "The 1/4 sec. cor. of secs. 16 and 21,									
	monumented with the decayed remains of a wooden post, firmly set and mkd. illegibly, and witnessed by the									
rema	remains of one of the original bearing trees.									
At t	At the corner point									
Set	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.									
		(1	T29N R31W 516 521 1963							

from which

The remains of the original bearing trees:

A stumphole, bears  $N50^{\circ}$ E, 37 lks. dist., remains of tree lying on ground, visible marks 1/4 S. (Record)

The new bearing trees:

A fir. 11 ins. diam., bears N35  $3/4^{\circ}$ E, 37 lks. dist., mkd. 1/4 S16 BT. A fir, 9 ins. diam.. bears S67  $1/4^{\circ}$ W, 12 lks. dist., mkd. 1/4 S21 BT.

Bury the remains of the original wooden post alongside of the iron post."

- II. Found an iron pipe, 2 1/2 ins. diam., 5 ins. above ground with a 3 1/4 ins. diam., B.L.M. brass cap marked as shown above, from which
  - A burnt fir snag, 12 ins. diam., bears  $N36^{\circ}E$ , 24.2 ft. dist., visible scribing 1/4 S16 BT.
  - A burnt fir snag, 9 ins. diam., bears \$70° w, 7.7 ft. dist., visible scribing \$21 BT.
- III. Attached Land Survey Monument and Bearing Tree signs on bearing trees. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, East, 3 ft. This corner lies in an old burned area, where new growth is about 6 ft. high and 2-3 ins. diameter. Therefore, no new accessories are established. Magnetic Declination: 20°30' East

