INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- topography was position in accessories, etc.


 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

_ T. ______ R. ____ 31 w. , P.M.M. , C-N-S 1/64 Lincoln Corner_ _County

- No previous record.
- II. No evidence found.
- III. At the calculated position shown by Certificate of Survey No. 2085 filed at Lincoln County Courthouse, Montana; set a 3/4 in. diam. by 30 ins. long aluminum rod, 26 ins. in the ground with 3 1/4" diam., U.S.D.A., Forest Service aluminum cap, marked as shown:




from which

A fir, 9 ins. diam., bears 86° , 51.3 ft. dist., mkd. C-N-S 1/64 BT. A fir, 8 ins. diam., bears $N43^{\circ}W$, 41.5 ft. dist., mkd. C-N-S 1/64 BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, East, 3 ft. Magnetic Declination: 20 East





<u> </u>	Sec. 14	4	
Office of Clerk and Recorder, County of American This "corner".			
record" was filed for record on July 23, 1993			
was noted on the cross-index plat and is assigned page No. 5349 , in	-		L — -
book NoBy DB		_ 👤 _	
County Official		j	

Cross Index No. _____ __ T, ____ R, ___ PMM

• - corner this sheet