

# CERTIFIED CORNER RECORDATION

CORNER 7 S1/4 S31 N1/4 S6 T. 30 N., R. 33 W., P.M.M. LINCOLN COUNTY

## RECORD:

Refer to attached GLO notes

## FOUND EVIDENCE:

A 5/8 inch dia. rebar capped with white plastic cap

A 18 inch DBH Hemlock with overgrown scribe bears S74°E 8.8 ft. dist.

A 12.5 inch DBH Cedar scribed 1/4 S6 T30N R33 BT bears N82°W 10.4 ft. dist.


## PERPETUATION:

Set a 2 1/2 inch dia. pipe 30 inches long 24 inches in the ground with a 3 1/4 inch Aluminum cap stamped (see diagram below)

MAGNETIC DECLINATION: 16° E

12.5" CEDAR

N 82° W  
10.4'



S 74° E  
8.8'

18" HEMLOCK

## CERTIFICATION

I, Clark Williams  
Certify the information shown herein is true and correct  
Signature of Ground Party Chief


I, David E. Williams  
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101 et seq., M.C.A.)

Signature of Surveyor & Seal  
Date: 12/10/2009 Reg. No. 19975-S  
Employer: Davis Surveying, Inc.

## SKETCH OF CORNER

Office of C 222801 BOOK: CCR CC&R'S PAGE: 11333 Pages: 1  
This "corne STATE OF MONTANA LINCOLN COUNTY  
was noted, RECORDED: 11/10/2009 3:47 KOI: CC&R'S  
No. TAMMY D. LAUER CLERK AND RECORDER  
In book No FEE: \$0.00 BY: Blairie Lauer Deputy  
TO: DAVIS SURVEYING, INC. P.O. BOX 896, TROY, MONTANA 59935

## SECTION



Cross Index No. T. 29 & 30 N., R. 34W., P.M.M.

THIS CORNER