CERTIFIED LAND CORNER RECORDATION

CORNERS IN SECTIONS 28 AND 29 TWP. 29 N., R. 33 W., M.P.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

CORNERS FOUND SHOWN ON DEAGRAM ON OTHER SIDE

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1973

CORNERS SET SHOWN ON DIAGRAM ON OTHER SIDE

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE OTHER SIDE

	-	
Surveyor's Seal	Jack H. Ninneman	DIAGRAM OF CORNER:
Surveyor 5 Sour	certify that the information shown herein is true and correct. Jack W. Rumena Signature of Ground Party Chief	N. (See other side)
	Jack W. Ninneman I, certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Signature of Surveyor	= Corner recorded on the sheet
	Montana Licanca #	521 F 9

Registration Number

Office of Clerk and Recorder, County of Jacoba	
2 nd	fundamental 1923, was noted on the cross-index plat and is
This "corner record" was filed for record on the day of	furting 19.42., was noted on the cross-index plat and is
assigned page No. 297 in book No.	Chanes L. Thughon By: Mae Watton
FORM 125 - 41483	Cross Index No. 5.8.1.1.2 T. 29 R. 33 Mer.
FURIN 123 - 41403	t 8+9

- Witness Corner found Brass Cap with 2 bearing trees on right side of road to Angel Island.
- Set a steel pin for E 1/16 from which a 10" Larch bears S 24 42' W 39.50 feet scribed E 1/16 S 29 and posted a 12" Larch bears N 19 W 34.30 feet #2 scribed E 1/16 Posted.
- #3 Set a steel pin for 1/16 W from which a 10" Cedar bears N 33 W 21.90 feet scribed W 1/16 S 21
- Set a steel pin for N 1/16 E from which a 28" Hemlock bears N 25° W 9.50 feet scribed N 1/16 E and posted an 18" Hemlock bears S 54° W 18.00 feet scribed N 1/16 E #4 and posted.
- Set a steel pin for 1/16 N from which an 18" Cedar bears S 63° W 14 feet scribed N 1/16 S 29 and posted. a 10" Hemlock bears S 44° E 16.50 feet scribed N 1/16 #5
- Set a steel pin for N 1/16 W from which a 16" pine bears N 35° W 16.30 feet an 8" Cedar bears N 65°E 6.5 feet #6 both scribed N 1/16 W and posted.
- Set a steel pin from which an 18" Cedar bears N 55°40' W 22.30 feet scribed C 1/16 E and posted
 A 30" Cedar bears S 11° E 11 30 feet scribed C 1/16 E and

