CERTIED CORNER RECORDATION

Corner N W Sec. Cor. S 1 T. 30 N., R. 26 W., P.M.M. Lincoln County

Record:

1932 original GLO notes by Ernest Parker.

The ground to bedrock, and in a mound of stone to top, for the cor. of Secs. 1 and 2 only, with brass cap.

A lodgepole pine, 8 ins. diam., bears S. 55 ° E., 45 lks. dist., marked T 30 N R 26 W S 1 B T.

A lodgepole pine, 9 ins. diam., bears S. 14 ½ ° W., 57 lks. dist.., marked T 30 N R 26 W S 2 B T.

Found Evidence:

Found iron pipe with brass cap. No evidence of Bearing Trees were found.

Perpetuation:

Established the following new Bearing Trees:

A douglas fir, 10 ins. diam., bears S. 31° E., 23.1 ft. dist., for Sec. 1.

A douglas fir, 17 ins. diam., bears S. 35° W., 29.4 ft. dist., for Sec. 2.

Painted 6 in. wide red bands around both Bearing Trees and attached Bearing Tree and warning signs.

Magnetic Declination: 17° E. 731N 536 730N R26W 52 51 17" Doug for 10" Doug for Sketch of Corner	SON REGWELBT	CERTIFICATION I, Ricky E. Shaver certify the information shown herein is true and correct Construction of the Party Chief I, Remember Dawis certify in this Corner Record correctly represents work performed in the corner Recordation of the Corner R
Sketch of Corner		Employer: Davis Surveying, Inc.

(ummus)

131

County Official

Office of Clerk and Recorder, County of

This "corner record" was filed for record on <u>2/29/2000</u> was noted on the cross-index plat and is assigned page No.

Section