

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the 1/4 corner common to Sections 16/15, T.30N., R.26W., P.M.M., Flathead County, Mont.

RECORD: Set a sandstone 24"x12"x8", 18 inches in the ground for 1/4 Sec. Cor., marked "1/4" on West face and raised a mound of stone 1-1/2 ft. high, 2 ft. base alongside - Pits impracticable - Trees too small to mark.

FOUND: No original evidence found.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 15 Oct 79

TO PERPETUATE THIS CORNER we set a 3" aluminum Berstein Monument 4" above the ground with rock and dirt mound, FROM WHICH:

- A 14" lodge pole pine bears: N.21°E., 20.0 feet, scribed 1/4 S15 RM
- A 14" lodge pole pine bears: S.75°W., 17.3 feet, marked 1/4 S16 RM

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. _____.

Surveyor's Seal

I, William Crockett
certify that the information shown herein is true and correct.

William Crockett

Signature of Ground Party Chief


I, R. David Schurian
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R. David Schurian
Signature of Surveyor


3102S

Registration Number

DIAGRAM OF CORNER:



= Corner recorded on the sheet



Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 24th day of December, 1979, was noted on the cross-index plat and is

signed page No. 560, in book No. 1

Eleanor L. Vaughan, by Betty Deere
County Official

Cross Index No. L-13 T. 30N R. 26W P.M.M. MM