CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

North Section Corner for Sections 15 and 16 only,

Record:

A limestone 10"x 8"x 8" above ground firmly set from which:

A tamarack 12" dia. bears S20-1/2°E, 53 lks A tamarack 14" dia. bears S71-3/4°W, 26 lks

Found:

Iron post with brass cap 8" above ground - mound of stone alongside

from which:

A 12" tamàrack stump bears S20-1/2°E, 35.0 ft A 14" tamarack stump bears S71-1/4°W, 17.2 ft

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1979

No additional monumentation needed.


NOTE: (Filed according to National Forest Records).

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey on file.

Surveyor's Seal



William Crockett

certify that the information shown herein is true and correct.

(1) Oliam Crochett

Signature of Ground Party Chief

R. David Schurian

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

S16 S15

= Corner recorded on the sheet

Registration Number

Sice of Clerk and Recorder, County of Lincoln	
ice of Clerk and Recorder, County of	1 / 10
a "corner record" was filed for record on the day of	Assembler 1929, was noted on the cross-index plat and is
igned page No 56/ , in book No /	County Difficial Detty Delegand
igned page No Que, in book No.	County Official County
•	Cross Index No. J-13 T 30 N. R 26 W. WXX

RM 12