## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1/4 Corner common to Sections 15 and 22, T.30 N., R.26 W., P.M.M.,

er common to sections is and ze, i.so his fitto his intitie

Record: Set a limestone 20"x 8"x 8", 15" in the ground for 1/4 Section Corner

marked 1/4 on N. face from which:

A spruce 8" dia. bears S17°W, 45 1ks A spruce 6" dia. bears N24°E, 19 1ks

Found:

3" BLM brass cap on 2-1/2" iron pipe 12" above ground from which:

A 12" lodge pole pine bears S39-3/4°E, 22.4 ft

A 13" spruce bears S15°W, 5.3 ft

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1979

No additional work needed.

NOTE: (Filed according to National Forest Records)

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey on file.

Surveyor's Seal



signed page No. 5762, in book No.

William Crockett

certify that the information shown herein is true and correct.

William Crockett

Signature of Ground Party Chief

ı, R. David Schurian

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.


R-Cavid Schurrey
Signature of Surveyor

3102S

Registration Number

DIAGRAM OF CORNER:

N.



= Corner recorded on the sheet

fice of Clerk and Recorder, County of Lineals

is "corner record" was filed for record on the 4th day of Assembles 1979, was noted on the cross-index plat and is

Cross Index No. N-15

T 30 N. R 26

County Official

W. 17.

RM 125