

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

North 1/4 Corner of Section 15 only, T.30 N., R.26 W., P.M.M.,

Record: Set an iron post 3 feet long, 1" dia., 28" in the ground for the 1/4 Corner of Section 15 only with brass cap from which:

A fir 5" dia. bears S60-1/4°E, 10 lks
A tamarack 6" dia. bears S34°W, 12 lks

Found: Iron post with 2" brass cap from which:

A 5" fir bears S60-1/4°E, 6.6 feet scribed 1/4 S15 BT
A tamarack down & rotted with scribing bears S34°W

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1979

No additional monumentation needed.

NOTE: (Filed according to National Forest Records).

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey on file.

DIAGRAM OF CORNER:

Surveyor's Seal


I, William Crockett
certify that the information shown herein is true and correct.

William Crockett
Signature of Ground Party Chief


I, R. David Schurian
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R. David Schurian
Signature of Surveyor

N.



= Corner recorded on the sheet



3102S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of December, 1979, was noted on the cross-index plat and is

signed page No. 564, in book No. 1

Eleanor L. Taugher, by Betty Beebe
County Official Deputy

Cross Index No. J-15 T. 30 N. R. 26 W. P.M.M. XXX