

# CERTIFIED LAND CORNER RECORDATION

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1/4 Corner common to Sections 15 and 14, T.30 W., R.26 W., P.M.M.,

Record: Set an iron post 3 ft. long, 1" dia., 14" in the ground to bedrock and in a mound of stone to top with brass cap marked as shown below from which:

A Lp. pine 14" dia. bears S44°E, 10 lks dist.

A Lp. pine 9" dia. bears S44°W, 21 lks dist.

Found: 1" dia. iron post with brass cap 10" above ground in a mound of stone from which:

A lodgepole pine 14" dia. bears S44°E, 6.6 ft

A lodgepole pine 9" dia. bears S44°W, down with scribing visible

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Oct. 1979


No additional monumentation needed.

NOTE: (Filed according to National Forest Records).

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey on file.

Surveyor's Seal



I, William Crockett  
certify that the information shown herein is true and correct.

William Crockett

Signature of Ground Party Chief

I, R. David Schurian  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.


R. David Schurian

Signature of Surveyor

3102S  
Registration Number

DIAGRAM OF CORNER:

N.



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of December, 1979, was noted on the cross-index plat and is

signed page No. 565, in book No. 1

Charles L. Douglas by Betty Bell  
County Official Deputy

Cross Index No. L-17 T. 30 N. R. 26 W. P.M.M. XXX