

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)


Found stone in place, marked as described (Record - Limestone 16" x 7", 11" in ground marked 1/4 on W. Face). Section 13 BT not found (Record - BT 9" fir marked 1/4 S BT bears S 79° E, 14 links). Section 14 BT found marked 1/4 balance of marking destroyed, (Record - 10" fir marked 1/4 S BT, bears N22°20' W, 47 links).

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/18/63

Set 2" iron pipe with brass cap marked as shown.

Blazed and engraved 28" larch marked F.S.R.M. 28.7' and S 72°E of 1/4 Sec. 14/13.



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

None

Surveyor's Seal

I,
certify that the information shown herein is true and correct.


.....
Signature of Ground Party Chief

I,
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Mona Berg
.....
Signature of Surveyor

1963.5
Registration Number

DIAGRAM OF CORNER:



= Corner recorded on the sheet

Office of Clerk and Recorder, County of LINCOLN, LIBBY, MONT.

This "corner record" was filed for record on the 8th. day of OCTOBER 1965, was noted on the cross-index plat and is assigned page No. 36, in book No. 1

M. M. MANSFIELD, By: *Verda Hiden*
County Official Deputy.

Cross Index No. L-21 T. 30 R. 27 Mer.