

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSH 5681.65)


DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found stone in place as marked. (Record - Limestone 20" x 12" x 6", 15" in ground marked with 4 notches on S. and 1 notch on E. edges.) Found Section 12 BT marked as described. (Record - 30" pine marked T30N, R27W, S 12 BT, bears N. 16°30' E., 269 links). Tree down Section 11 B.T. (Record - 24" tamarack marked T30NR27W S. 11 BT, bears N 18°, 256 links). Stump found Section 13 BT (Record 24" pine marked T30N R27W Section 13 BT, bears S 77°30' East, 125 links). Found Section 14 BT marked as described (Record - 26" pine marked T30N, R27W, Section 14 BT, bears S 47° W, 159 links).

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7/18/63

Placed stone to south of pipe with brass cap.
Set 2" pipe with brass cap stamped as shown.
New BT 10" pine marked F.S.R.M. bears S 56° E, 24.2'
New BT 12" pine marked F.S.R.M. bears N 39°30' W, 40.55'

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

None

Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, _____
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Norman Berg
Signature of Surveyor

DIAGRAM OF CORNER:

N. T30N, R27W



= Corner recorded on the sheet

19635
Registration Number

Office of Clerk and Recorder, County of LINCOLN, LIBBY, MONT.

This "corner record" was filed for record on the 8th day of OCTOBER, 1965, was noted on the cross-index plat and is assigned page No. 37, in book No. 1

M. M. MANSFIELD, By: *Leslie Hyden*
County Official Deputy.

Cross Index No. J-21 T. 30 R. 27 Mer.