CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing TWP corner common to Sec. 36 and 1, T.30 and 29N., R.28W. MPM. Found original stone loosely set and marked (record--set a slate stone, $16 \times 14 \times 9$ ins., 11 ins. in the ground, for NE cor. of T.29N., R. 28W., marked with 6 notches on S. and W. edges) from which:

A fir, 32 ins. diam, bears S.30°W - 100 Lks. Dist., Stump (burned blaze). (Record - a fir, 30 ins. diam., bears S.30°W - 100 Lks. Dist., marked T.29N., R.28W. S 1 BT)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

For the closing TWP corner common to Sec. 36 and 1, T.30 and 29N. $R.28W.\ MPM.\ I$ set a 2 in. galvanized iron pipe 24 ins. in the ground, with brass cap marked, I set corner from record bearing and distance, from which:

A 8 in. Douglas fir bears N. 9-3/40 W - 44 Lks. Dist. marked RM.

I placed signs and paint on RM and at corner.

Date of work: Oct.4,1971 T30N R28W S 36 T29N S 6 S **R27W** 1 T29N R28W SJS 2532 S 1971

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal

I, A. R. Trenkle and Joe French certify that the information shown herein is true and correct.

a.R.Ti

Signature of Ground Party Chief

I, Stanley J. Skousen certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> ley Signature of Sur

DIAGRAM OF CORNER:

T30N **R28W** S 36 S T29N R28W

c = Corner recorded on the sheet

2532-S Registration Number

Office of Clerk and Recorder, County of Lineals This "corner record" was filed for record on the 19.//..., was noted on the cross-index plat and is . day of o assigned page No. 236, in book No...