

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 5 and 6, T30N, R28W, MPM, found original brass cap firmly set and marked (record - set A 2" iron pipe, 28" in the ground with brass cap marked) from which:

A pine, 10 ins. diam, bears S 12° E., 17 Lks. Dist. snag with scribing visible.
(Record - A pine, 9 ins. diam, bears S 55° E., 17 Lks. Dist., marked T30N, R28W S 5 CC BT)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

For the closing corner common to Sec. 5 and 6, T30N, R28W, MPM,
I raised a collar of stone, three foot base, 10 ins. high around
the original iron pipe.
From which: New RM's

A 6 in. Douglas Fir bears S 44½° E - 22 Lks. Dist.
Marked RM

A 11 in. Douglas Fir bears S 1¼° W - 30 Lks. Dist.
Marked RM

I placed signs and paint on RM's and at corner.

Date of work:.....

T 31 N R 28 W
S 31
S 6 | S 5
T 30 N
R 28 W
1929
(BRASS CAP)

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal

I, A. R. Trenkle and Joe French
certify that the information shown herein is true and
correct.

A. R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same.

Stanley J. Skousen

Signature of Surveyor

DIAGRAM OF CORNER:

N. T 31 N R 28 W
S 31
S 6 | S 5
T 30 N R 28 W
CC

▼ = Corner recorded on the sheet

2532-S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 27th day of February 1973, was noted on the cross-index plat and is

assigned page No. 290, in book No. 1

Eleanor L. Vaughn, Esq. Max Watson, Esq.
County Official

Cross Index No. A-5 T. 30 R. 28 Mer.