INSTRUCTIONS

- ription of evidence found, note discrepencies in the record, state method of establishing fost or obliterated corners.
- tion of monument and accessories set to perpetuate the corner posi
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, p
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner CN1/16 SEC. 9 T. 30N R. 29W P.M.M. <u>Lincoln</u> ____ County **ORIGINAL:**

NONE

FOUND:

Found: 3 1/4" Aluminum cap, Corp of Engineering Cap "102-1" And a metal post 1' south.

**** Corp cap is N54-06-29E, 0.59' distance from computed CN 1/16 position ****** Accept Corp cap for CN 1/16

A 9" Fir, bears S15 1/4W, 22.56' dist., scribed: CN 1/16 S9 BT, with BT tag A 12" Fir, bears S49 1/4E, 33.56' dist., scribed: CN 1/16 S9 BT, with BT tag



SKETCH OF CORNER

CERTIFICATION

James R. Staples Certify the information shown herein is true and correct.

amer Signature Ground Party Chief

James R. Staples

rtify that this Corner Record correctly represents me or under my direction in compliance

Act" (70-22-101, et seq., M.C.A.)


Signature of Surveyor & Se

Reg. No. 99581

Employer: <u>J.R.S. Surveying, Inc.</u>

Office of Clerk and Recorder, County of This "corner 206766 BOOK: CCR CCGR'S PAGE: 11136 Pages: 1 record" was filed for record c STATE OF MONTANA LINCOLN COUNTY was noted on the cross-index TAMMY D. LAUER CLERK AND RECORDER RECORDED: 10/16/2007 9:17 KOI: CCGR'S FEE: \$0.00 book no. BY: TO: J.R.S. BURVEYING P. 6 SOX 1050, LIBBY, MONTANA 59923 County Official

> Cross Index No. F11 T. 30N R. 29W PMM Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors



JAMES R.

STAPLES 9958 LS